

# TDS



## Waterproof Masking Tape Green

November 2024

Product Code:	BWMTG19 / 38 / 48
Revision Date:	14.11.24
Revision Number:	01
Company & Address:	PPG Industries UK) Ltd Needham Road, Stowmarket, Suffolk IP14 2AD, U.K. PPG Industries Italia S.r.l. Via Comasina, 121 - 20161 Milano - Italy
Telephone:	Tel: +44 (0) 1449 773338 / Tel. (+39).02.6404.1

### Part Numbers:

Part No.	Description
<b>BWMTG19</b>	Waterproof Masking Tape Green 19mm x 50m (Box of 48)
<b>BWMTG38</b>	Waterproof Masking Tape Green 38mm x 50m (Box of 24)
<b>BWMTG48</b>	Waterproof Masking Tape Green 48mm x 50m (Box of 20)



### Description:

Bodyline Waterproof masking tape green is ideal for car refinish applications. The product consists of a green coloured, waterproof saturated crepe paper masking tape with a custom formulated rubber-based adhesive. The product provides good adhesion on uneven surfaces and will hold to and cleanly remove from various surfaces, residue-free removal if removed as soon as paint is dry, even when exposed to temperatures up to 90°C for up to 30 mins.

**Physical Properties:** Values shown are typical values and not to be used for specication purposes.

Carrier	Waterproof saturated crepe paper
Adhesive	Natural Rubber / Resins
Colour	Green
Adhesion	4,8 N/25mm
Elongation to break	8%
Temperature Resistance	90°C f
Recommended time of temperature resistance	30 minutes
Tensile strength	90 N/25mm
Thickness	0.130mm
Width	19mm, 38mm and 48mm
Weight of the backing	63 g/m <sup>2</sup>
Removal time	Recommended to be removed within 48 hours



Product shelf life and storage: 12 months; suggested storage temperature shall range from 15°C to 25°C with max. relative humidity of 65%. Material shall be stored away from heat sources and possibly kept in original package, avoiding light exposure as well. When temperatures are lower than suggested, it is always required to recondition the tape at normal temperature before use.

**This data sheet is compiled to be of assistance but without guarantee. Users are responsible for safe working practices and PPE requirements. Final determination of suitability of any material is the sole responsibility of the user. For professional use only.**