

## TEROSON® BOND GLASS CLEANER

Known as TEROSON® VR 100  
August 2020**PRODUCT DESCRIPTION**

TEROSON® BOND GLASS CLEANER provides the following product characteristics:

<b>Technology</b>	Glass cleaner
Chemical Type	Water based tensides
Appearance (uncured)	Bluish liquid
Components	One-component – requires no mixing
Viscosity	Liquid
<b>Cure</b>	Not applicable
<b>Application</b>	Surface preparation
Environmental temperature at application	-5 to 45°C (23 to 113°F)
Material application temperature	5 to 35°C (41 to 95°F)
Specific Benefits	<ul style="list-style-type: none"> <li>• High cleaning properties in combination with TEROSON® BOND SPONGE</li> <li>• Solvent free</li> <li>• Simple process</li> </ul>

TEROSON® BOND GLASS CLEANER is suitable for all surfaces of the vehicle, especially glass and plexiglas. Removes dust, dirt and all common contaminants and evaporates to a streak- and residue-free shine. Apply with a lint-free cloth. In combination with TEROSON BOND SPONGE, it is ideal to efficiently clean the bondline prior to windscreen bonding. Typical applications include the bonding of front, rear and side screens to the body of passenger-, utility-, special- and rail vehicles.

**TYPICAL PROPERTIES**

Specific Gravity @23°C 0.99

**GENERAL INFORMATION**

This product is not recommended for use in pure oxygen and/or oxygen rich systems and should not be selected as a sealant for chlorine or other strong oxidizing materials.

For safe handling information on this product, consult the Safety Data Sheet (SDS).

**Direction For Use****Application**

TEROSON® BOND GLASS CLEANER is applied directly on the windscreen and wiped off in one direction with a clean lint free cloth. The bondline should be ideally prepared in combination with the wetted TEROSON® BOND SPONGE by wiping back and forth to achieve best preparation. The pretreatment products / adhesives can be applied after evaporation.

**Storage**

Store product in the unopened container in a dry location. Storage information may also be indicated on the product container labelling.

**Optimal Storage: 5 to 30 °C. Storage below 5 °C or greater than 30 °C can adversely affect product properties.**

Material removed from containers may be contaminated during use. Do not return product to the original container. Henkel Corporation cannot assume responsibility for product which has been contaminated or stored under conditions other than those previously indicated. If additional information is required, please contact your local Henkel representative.

**Product Specification:**

The technical data contained herein are intended as reference only and are not considered specifications for the product. Product specifications are located on the Certificate of Analysis or please contact Henkel representative.

**Approval and Certificate:**

Please contact a Henkel representative for related approval or certificate of this product.

**Data Ranges**

The data contained herein may be reported as a typical value. Values are based on actual test data and are verified on a periodic basis.

Temperature/Humidity Ranges: 23 °C / 50% RH = 23 $\pm$ 2 °C / 50 $\pm$ 5% RH

**Conversions:**

(°C x 1.8) + 32 = °F  
kV/mm x 25.4 = V/mil  
mm / 25.4 = inches  
μm / 25.4 = mil  
N x 0.225 = lb  
N/mm x 5.71 = lb/in  
N/mm<sup>2</sup> x 145 = psi  
MPa x 145 = psi  
N·m x 8.851 = lb·in  
N·m x 0.738 = lb·ft  
N·mm x 0.142 = oz·in  
mPa·s = cP

**Disclaimer:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. The product can have a variety of different applications as well as differing application and working conditions in your environment that are beyond our control. Henkel is, therefore, not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product. Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Belgium NV, Henkel Electronic Materials NV, Henkel Nederland BV, Henkel Technologies France SAS and Henkel France SA please additionally note the following:**

In case Henkel would be nevertheless held liable, on whatever legal ground, Henkel's liability will in no event exceed the amount of the concerned delivery.

**In case products are delivered by Henkel Colombian, S.A.S. the following disclaimer is applicable:**

The information provided in this Technical Data Sheet (TDS) including the recommendations for use and application of the product are based on our knowledge and experience of the product as at the date of this TDS. Henkel is not liable for the suitability of our product for the production processes and conditions in respect of which you use them, as well as the intended applications and results. We strongly recommend that you carry out your own prior trials to confirm such suitability of our product.

Any liability in respect of the information in the Technical Data Sheet or any other written or oral recommendation(s) regarding the concerned product is excluded, except if otherwise explicitly agreed and except in relation to death or personal injury caused by our negligence and any liability under any applicable mandatory product liability law.

**In case products are delivered by Henkel Corporation or Henkel Canada, Inc. the following disclaimer is applicable:**

The data contained herein are furnished for information only and are believed to be reliable. We cannot assume responsibility for the results obtained by others over whose methods we have no control. It is the user's responsibility to determine suitability for the user's purpose of any production methods mentioned herein and to adopt such precautions as may be advisable for the protection of property and of persons against any hazards that may be involved in the handling and use thereof. In light of the foregoing, **Henkel Corporation specifically disclaims all warranties expressed or implied, including warranties of merchantability or fitness for a particular purpose, arising from sale or use of Henkel Corporation's products. Henkel Corporation specifically disclaims any liability for consequential or incidental damages of any kind, including lost profits.** The discussion herein of various processes or compositions is not to be interpreted as

representation that they are free from domination of patents owned by others or as a license under any Henkel Corporation patents that may cover such processes or compositions. We recommend that each prospective user test his proposed application before repetitive use, using this data as a guide. This product may be covered by one or more United States or foreign patents or patent applications.

**Trademark usage**

Except as otherwise noted, all trademarks in this document are trademarks of Henkel Corporation in the U.S. and elsewhere.® denotes a trademark registered in the U.S. Patent and Trademark Office.

Reference 0.0



For the most direct access to local sales and technical support visit: [www.henkel.com/industrial](http://www.henkel.com/industrial)